

WT and DA

Assignment-1)

Q. 1) Write a PHP script to keep track of number of times the web page has been accessed (Use Session Tracking).

Ans:

```
<?php
Session_start();

If(isset($_SESSION['pcount'])) {
    $_SESSION['pcount'] += 1;
} else {
    $_SESSION['pcount'] = 1;
}

Echo "You have visited this page ".$_SESSION['pcount']." Time(s).";
?>
```

Q. 2) Create 'Position_Salaries' Data set. Build a linear regression model by identifying independent and

Target variable. Split the variables into training and testing sets. Then divide the training and testing sets

Into a 7:3 ratio, respectively and print them. Build a simple linear regression model. Ans:

Import numpy as np



```

Import pandas as pd
From sklearn.model_selection import train_test_split
From sklearn.linear_model import LinearRegression

# Create the Position_Salaries dataset
Data = {'Position': ['CEO', 'charman', 'director', 'Senior Manager', 'Junior Manager', 'Intern'],
        'Level': [1, 2, 3, 4, 5, 6],
        'Salary': [50000, 80000, 110000, 150000, 200000, 250000]}
Df = pd.DataFrame(data)

# Identify the independent and target
variables X = df.iloc[:, 1:2].values
Y = df.iloc[:, 2].values

# Split the variables into training and testing sets with a 7:3 ratio
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random_state=0)

# Print the training and testing sets
Print("X_train:\n", X_train)
Print("y_train:\n", y_train)
Print("X_test:\n", X_test)
Print("y_test:\n", y_test)

# Build a simple linear regression model
Regressor = LinearRegression()
Regressor.fit(X_train, y_train)

# Print the coefficients and intercept
Print("Coefficients:", regressor.coef_)

```



```
Print("Intercept:", regressor.intercept_)
```

Assignment-2)

Q. 1 Write a PHP script to change the preferences of your web page like font style, font size, font color,

Background color using cookie. Display selected setting on next web page and actual implementation

(with new settings) on third page (Use Cookies).

Ans :

Fristpage.html

```
<!DOCTYPE html>
<html>
<head>
    <title>Change preferences</title>
</head>
<body>
    <h1>Change preferences</h1>
    <form action="secondpage.php" method="post">
        <label for="fontstyle">Font Style:</label>
        <select name="fontstyle" id="fontstyle">
            <option value="Arial">Arial</option>
            <option value="Times New Roman">Times New Roman</option>
            <option value="Verdana">Verdana</option>
        </select><br><br>
```



```
<label for="fontsize">Font Size:</label>
<select name="fontsize" id="fontsize">
    <option value="12">12</option>
    <option value="14">14</option>
    <option value="16">16</option>
</select><br><br>
<label for="fontcolor">Font Color:</label>
<input type="color" name="fontcolor" id="fontcolor"><br><br>
<label for="bgcolor">Background Color:</label>
<input type="color" name="bgcolor" id="bgcolor"><br><br>
<input type="submit" name="submit" value="Save">
</form>
</body>
</html>
```

Secondpage.php

```
<?php
If(isset($_POST['submit'])) {
    $fontstyle = $_POST['fontstyle'];
    $fontsize = $_POST['fontsize'];
    $fontcolor = $_POST['fontcolor'];
    $bgcolor = $_POST['bgcolor'];

    // Set the cookie values
    Setcookie('fontstyle', $fontstyle, time()+86400);
    Setcookie('fontsize', $fontsize, time()+86400);
    Setcookie('fontcolor', $fontcolor,
time()+86400); Setcookie('bgcolor', $bgcolor,
time()+86400);
```



```
// Redirect to the next page
Header('Location: thirdpage.php');
Exit();
}
?>
```

Thirdpage.php

```
<?php
// Retrieve the cookie values
$fontstyle = isset($_COOKIE['fontstyle']) ? $_COOKIE['fontstyle'] : 'Arial';
$fontsize = isset($_COOKIE['fontsize']) ? $_COOKIE['fontsize'] : '12';
$fontcolor = isset($_COOKIE['fontcolor']) ? $_COOKIE['fontcolor'] : '#000000';
$bgcolor = isset($_COOKIE['bgcolor']) ? $_COOKIE['bgcolor'] : '#FFFFFF';
?>
```

```
<!DOCTYPE html>
<html>
<head>
<title>Page with new settings</title>
<style
type="text/css
"> Body {
Font-family: <?php echo $fontstyle
?>; Font-size: <?php echo $fontsize
?>px; Color: <?php echo
$fontcolor ?>;
} Background-color: <?php echo $bgcolor ?>;
</style>
```



```
</head>
<body>
    <h1>Page with new settings</h1>
    <p>This is the page with the new settings. The font style is <?php echo $fontstyle
?>, the font size is <?php echo $fontsize ?>px, the font color is <?php echo $fontcolor ?>,
and the background color is <?php echo $bgcolor ?>.</p>
</body>
</html>
```

Q. 2) Create 'Salary' Data set . Build a linear regression model by identifying independent and target

Ariable. Split the variables into training and testing sets and print them. Build a simple linear regression

Del for predicting purchases.

Ans:

```
Import numpy as
```

```
np Import pandas
```

```
as pd
```

```
From sklearn.model_selection import train_test_split
```

```
From sklearn.linear_model import LinearRegression
```

```
# Create the Salary dataset
```

```
Data = {'YearsExperience': [1, 2, 3, 4, 5, 6, 7, 8, 9, 10],
```

```
    'Salary': [50000, 60000, 70000, 80000, 90000, 100000, 110000, 120000, 130000, 140000]}
```

```
Df = pd.DataFrame(data)
```

```
# Identify the independent and target
```

```
variables X = df.iloc[:, 0:1].values
```



```
Y = df.iloc[:, 1].values
```

```
# Split the variables into training and testing sets
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random_state=0)
```

```
# Print the training and testing sets
```

```
Print("X_train:\n", X_train)
```

```
Print("y_train:\n", y_train)
```

```
Print("X_test:\n", X_test)
```

```
Print("y_test:\n", y_test)
```

```
# Build a simple linear regression model
```

```
Regressor = LinearRegression()
```

```
Regressor.fit(X_train, y_train)
```

```
# Print the coefficients and
```

```
intercept Print("Coefficients:",
```

```
regressor.coef_) Print("Intercept:",
```

```
regressor.intercept_)
```

Assignment-3)

Q. 1) Write a PHP script to accept username and password. If in the first three chances, username and

Password entered is correct then display second form with "Welcome message" otherwise display error

Message. [Use Session]

.



Ans:

```
<?php
```

```
// Start session
```

```
Session_start();
```

```
// Check if login form has been submitted
```

```
If(isset($_POST['submit'])) {
```

```
    // Get username and password input from user
```

```
    $username = $_POST['username'];
```

```
    $password = $_POST['password'];
```

```
    // Set correct username and password
```

```
    $correct_username = 'myusername';
```

```
    $correct_password = 'mypassword';
```

```
// Check if entered username and password are correct
```

```
If($username == $correct_username && $password == $correct_password) {
```

```
    // Set session variable to mark user as logged in
```

```
    $_SESSION['loggedin'] = true;
```

```
    // Redirect user to welcome
```

```
page      Header('Location:
```

```
welcome.php'); Exit;
```

```
} else {
```

```
    // Decrement login attempts
```

```
If(isset($_SESSION['attempts']))
```

```
{
```

```
    $_SESSION['attempts']--;
```

```
} else {
```



```

    $_SESSION['attempts'] = 3;
}

// Display error message if maximum login attempts exceeded
If($_SESSION['attempts'] <= 0) {
    Echo "Maximum login attempts exceeded. Please try again later.";
} else {
    // Display error message
    Echo "Invalid username or password. You have ".$_SESSION['attempts']." Attempt(s) left.";
}
}
}
?>

```

```

<!--HTML form for user input □
<form method="post">
    <label for="username">Username:</label>
    <input type="text" id="username" name="username" required><br><br>

    <label for="password">Password:</label>
    <input type="password" id="password" name="password" required><br><br>

    <input type="submit" name="submit" value="Log In">
</form>

```

Q. 2) Create 'User' Data set having 5 columns namely: User ID, Gender, Age, Estimated Salary and purchased. Build a logistic regression model that can predict whether on the given parameter a person will buy a car or not.

Ans:

Import pandas as pd

```
Data = {'User ID': [1, 2, 3, 4, 5, 6, 7, 8, 9, 10],  
        'Gender': ['Male', 'Male', 'Female', 'Female', 'Male', 'Male', 'Female', 'Female', 'Male',  
        'Female'], 'Age': [19, 35, 26, 27, 19, 27, 32, 25, 33, 45],  
        'Estimated Salary': [19000, 20000, 43000, 57000, 76000, 58000, 82000, 32000, 69000,  
        65000],  
        'Purchased': [0, 0, 0, 1, 1, 0, 1, 0, 1, 1]}
```

Df = pd.DataFrame(data)

From sklearn.model_selection import train_test_split

```
X = df.iloc[:,  
1:4].values Y =  
df.iloc[:, 4].values
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3,  
random_state=0) From sklearn.linear_model import LogisticRegression
```

```
Lr=LogisticRegression(random_state  
=0) Lr.fit(X_train, y_train)
```

Predict a single observation

```
Observation = [[0, 30, 87000]]
```

Prediction =

```
Lr.predict(observation)
```

```
Print(prediction)
```

Predict multiple observations



Observations = [[0, 30, 87000], [1, 50, 45000], [1, 22, 30000]]

Predictions = Lr.predict(observations)

Print(predictions)

Assignment-4)

**Q. 1) Write a PHP script to accept Employee details (Eno, Ename, Address) on first page.
On second**

**Page accept earning (Basic, DA, HRA). On third page print Employee information (Eno,
Ename, Address,**

Basic, DA, HRA, Total) [Use Session]

.

Ans:

Firstpage.php

<?php

Session_start();

?>

<!DOCTYPE html>

<html>

<head>

<title>Employee Details</title>

</head>

<body>

<h1>Employee Details</h1>



```

<form method="POST" action="Secondpage.php">
    <label for="eno">Employee No:</label>
    <input type="text" id="eno" name="eno"><br><br>
    <label for="ename">Employee Name:</label>
    <input type="text" id="ename" name="ename"><br><br>
    <label for="address">Address:</label>
    <textarea id="address" name="address"></textarea><br><br>
    <input type="submit" value="Next">
</form>
</body>
</html>

<?php
// Store employee details in session
If(isset($_POST['eno']) && isset($_POST['ename']) && isset($_POST['address'])) {
    $_SESSION['eno'] = $_POST['eno'];
    $_SESSION['ename'] = $_POST['ename'];
    $_SESSION['address'] = $_POST['address'];
}
?>

```

Secondpage.php

```

<?php
Session_start();
?>

<!DOCTYPE html>
<html>

```



```

<head>
    <title>Earnings</title>
</head>
<body>
    <h1>Earnings</h1>
    <form method="POST" action="thirdpage.php">
        <label for="basic">Basic:</label>
        <input type="text" id="basic" name="basic"><br><br>
        <label for="da">DA:</label>
        <input type="text" id="da" name="da"><br><br>
        <label for="hra">HRA:</label>
        <input type="text" id="hra" name="hra"><br><br>
        <input type="submit" value="Next">
    </form>
</body>
</html>

<?php
// Store earnings in session
If(isset($_POST['basic']) && isset($_POST['da']) && isset($_POST['hra'])) {
    $_SESSION['basic'] = $_POST['basic'];
    $_SESSION['da'] = $_POST['da'];
    $_SESSION['hra'] = $_POST['hra'];
}
?>

```

Thirdpage.php

```

<?php
Session_start();

// Calculate total earnings
$total = $_SESSION['basic'] + $_SESSION['da'] + $_SESSION['hra'];
?>

<!DOCTYPE html>
<html>
<head>
    <title>Employee Information</title>
</head>
<body>
    <h1>Employee Information</h1>
    <p><strong>Employee No:</strong> <?php echo $_SESSION['eno']; ?></p>
    <p><strong>Employee Name:</strong> <?php echo $_SESSION['ename']; ?></p>
    <p><strong>Address:</strong> <?php echo $_SESSION['address']; ?></p>
    <p><strong>Basic:</strong> <?php echo $_SESSION['basic']; ?></p>
    <p><strong>DA:</strong> <?php echo $_SESSION['da']; ?></p>
    <p><strong>HRA:</strong> <?php echo $_SESSION['hra']; ?></p>
    <p><strong>Total Earnings:</strong> <?php echo $total; ?></p>
</body>
</html>

```

Q. 2) Build a simple linear regression model for Fish Species Weight

Prediction. Ans:

Import pandas as pd

Import random

From sklearn.linear_model import LinearRegression

create the dataset

Fish_species = ['Tuna', 'Salmon', 'Trout', 'Bass', 'Sardine', 'Cod', 'Mackerel']

Weights = []

For i in

range(50):

Fish_weight =

[] For j in

range(7):

**Weight = random.randint(1,
20)**

Fish_weight.append(weight)

Weights.append(fish_weight)

Df = pd.DataFrame(weights, columns=fish_species)

create the linear regression model

X = df.iloc[:, :-1] # independent

variables Y = df.iloc[:, -1] # target

variable

Model = LinearRegression()

Model.fit(X, y)

predict the weight of a new fish species

New_fish = [[10, 12, 15, 7, 4, 8]] # example input

Predicted_weight = model.predict(new_fish)

Print("Predicted weight:", predicted_weight)



Assignment-5)

Q. 1) Create XML file named "Item.xml" with item-name, item-rate, item quantity Store the details of 5

Items of different Types.

Ans:

Item.xml

```
<items>
```

```
  <item type="Electronics">
```

```
    <name>Television</name>
```

```
    <rate>500</rate>
```

```
    <quantity>10</quantity>
```

```
  </item>
```

```
  <item type="Clothing">
```

```
    <name>Shirt</name>
```

```
    <rate>50</rate>
```

```
    <quantity>20</quantity>
```

```
  </item>
```

```
  <item type="Grocery">
```

```
    <name>Rice</name>
```

```
    <rate>40</rate>
```

```
    <quantity>30</quantity>
```

```
  </item>
```

```
  <item type="Books">
```

```
    <name>Harry Potter and the Philosopher's Stone</name>
```

```
    <rate>20</rate>
```

```
    <quantity>50</quantity>
```

```
  </item><item type="Sports">
```



```
<name>Football</name>
<rate>100</rate>
<quantity>5</quantity>
</item>
</items>
```

Q. 2) Use the iris dataset. Write a Python program to view some basic statistical details like percentile,

Mean, std etc. Of the species of 'Iris-setosa', 'Iris-versicolor' and 'Iris-virginica'. Apply logistic regression

On the dataset to identify different species (setosa, versicolor, virginica) of Iris flowers given just 4

Features: sepal and petal lengths and widths.. Find the accuracy of the model. Ans:

```
Import pandas as pd
From sklearn.datasets import load_iris
From sklearn.linear_model import
LogisticRegression From sklearn.model_selection
import train_test_split From sklearn.metrics import
accuracy_score

# load the iris dataset
Iris = load_iris()

# create a dataframe from the dataset
Df = pd.DataFrame(iris.data, columns=iris.feature_names)
Df['target'] = iris.target
```

```
# view basic statistical details of the different  
species Print("Statistical details of Iris-setosa:")  
Print(df[df['target']==0].describe())  
  
Print("Statistical details of Iris-  
versicolor:")  
Print(df[df['target']==1].describe())  
  
Print("Statistical details of Iris-virginica:")  
Print(df[df['target']==2].describe())  
  
# split the data into training and testing  
sets X = df.iloc[:, :-1]  
Y = df.iloc[:, -1]  
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)  
  
# fit a logistic regression model  
Logreg = LogisticRegression()  
Logreg.fit(X_train, y_train)  
  
# make predictions on the test set  
Y_pred = logreg.predict(X_test)  
  
# calculate the accuracy of the model  
Accuracy = accuracy_score(y_test, y_pred)  
Print("Accuracy of the logistic regression model:", accuracy)
```



Assignment-6)

Q. 1) Write PHP script to read "book.xml" file into simpleXML object. Display attributes and elements .

(simple_xml_load_file() function)

.

Ans:

```
<?php
```

```
// Load the XML file into a SimpleXML object
```

```
$xml = simplexml_load_file("book.xml");
```

```
// Display the attributes and elements of the SimpleXML
```

```
object Echo "Book attributes: <br>";
```

```
Echo "ISBN: " . $xml['isbn'] . "<br>";
```

```
Echo "Publisher: " . $xml['publisher'] .
```

```
"<br>"; Echo "<br>";
```

```
Echo "Book elements: <br>";
```

```
Echo "Title: " . $xml->title .
```

```
"<br>";
```

```
Echo "Author: " . $xml->author . "<br>";
```

```
Echo "Description: " . $xml->description . "<br>";
```

```
?>
```

Book.xml file

```
<?xml version="1.0"?>
```

```
<book isbn="978-3-16-148410-0" publisher="Example Publisher">
```

```
<title>Example Book</title>
```

```
<author>John Doe</author>
```

```
<description>This is an example book.</description>
```



</book>

Q. 2) Create the following dataset in python & Convert the categorical values into numeric format. Apply

The apriori algorithm on the above dataset to generate the frequent itemsets and association rules. Repeat

Te process with different min_sup values.

TID={1:["bread","milk"],2:["bread","diaper","beer","eggs"],3:["milk","diaper","beer","coke"],4:["bread","milk","diaper","beer"],5:["bread","milk","diaper","coke"]}

Ans:

Import pandas as pd

From mlxtend.preprocessing import TransactionEncoder

From mlxtend.frequent_patterns import apriori, association_rules

create the dataset

TID =

{1:["bread","milk"],2:["bread","diaper","beer","eggs"],3:["milk","diaper","beer","coke"],4:["bread","milk","diaper","beer"],5:["bread","milk","diaper","coke"]}

Transactions = []

For key, value in TID.items():

Transactions.append(value)

convert the categorical values into numeric

format Te = TransactionEncoder()

Te_ary = te.fit_transform(transactions)

Df = pd.DataFrame(te_ary, columns=te.columns_)



```

# apply the apriori algorithm with different min_sup
values Min_sup_values = [0.2, 0.4, 0.6]
For min_sup in min_sup_values:
    Frequent_itemsets = apriori(df, min_support=min_sup, use_colnames=True)
    Rules = association_rules(frequent_itemsets, metric="confidence", min_threshold=0.7)
    Print("Min_sup:", min_sup)
    Print("Frequent Itemsets:")
    Print(frequent_itemsets)
    Print("Association Rules:")
    Print(rules)

```

Assignment-7)

Q. 1) Write a PHP script to read "Movie.xml" file and print all MovieTitle and ActorName of file using

OMDocument Parser. "Movie.xml" file should contain following information with at least 5 records

With values. MovieNo, MovieTitle, ActorName, ReleaseYear.

Ans:

Php file

```

<?php
// Load the XML file
$xml = new DOMDocument();
$xml->load('Movie.xml');

```

```

// Get all the movie nodes
$movies = $xml->getElementsByTagName('MovieInfo');

// Loop through each movie node and print the movie title and actor name

Foreach ($movies as $movie) {
    Echo "Movie Title: " . $movie->getElementsByTagName('MovieTitle')[0]->textContent . " ,
    "; Echo "Actor Name: " . $movie->getElementsByTagName('ActorName')[0]->textContent .
    "<br>";
}
?>

```

XML file

```

<?xml version="1.0"?>
<MovieList>
    <MovieInfo>
        <MovieNo>1</MovieNo>
        <MovieTitle>The Shawshank Redemption</MovieTitle>
        <ActorName>Tim Robbins</ActorName>
        <ReleaseYear>1994</ReleaseYear>
    </MovieInfo>
    <MovieInfo>
        <MovieNo>2</MovieNo>
        <MovieTitle>The Godfather</MovieTitle>
        <ActorName>Marlon Brando</ActorName>
        <ReleaseYear>1972</ReleaseYear>
    </MovieInfo>
    <MovieInfo>

```



```
<MovieNo>3</MovieNo>
<MovieTitle>The Dark Knight</MovieTitle>
<ActorName>Christian Bale</ActorName>
<ReleaseYear>2008</ReleaseYear>
</MovieInfo>
<MovieInfo>
  <MovieNo>4</MovieNo>
  <MovieTitle>The Godfather: Part II</MovieTitle>
  <ActorName>Al Pacino</ActorName>
  <ReleaseYear>1974</ReleaseYear>
</MovieInfo>
<MovieInfo>
  <MovieNo>5</MovieNo>
  <MovieTitle>12 Angry Men</MovieTitle>
  <ActorName>Henry Fonda</ActorName>
  <ReleaseYear>1957</ReleaseYear>
</MovieInfo>
</MovieList>
```

Q. 2) Download the Market basket dataset. Write a python program to read the dataset and display its

Information. Preprocess the data (drop null values etc.) Convert the categorical values into numeric

Format. Apply the apriori algorithm on the above dataset to generate the frequent itemsets and association

Rules. .

Ans:

```
Import pandas as pd  
From mlxtend.preprocessing import TransactionEncoder  
From mlxtend.frequent_patterns import apriori, association_rules  
  
# read the dataset  
Df = pd.read_csv('Market_Basket_Optimisation.csv', header=None)  
  
# drop null values  
Df.dropna(inplace=True)  
e)  
  
# convert categorical values to numeric using one-hot  
encoding Te = TransactionEncoder()  
Te_ary = te.fit(df.values).transform(df.values)  
Df = pd.DataFrame(te_ary, columns=te.columns_)  
  
# generate frequent itemsets using apriori algorithm  
Frequent_itemsets = apriori(df, min_support=0.01,  
use_colnames=True)  
  
# generate association rules from frequent itemsets  
Rules = association_rules(frequent_itemsets, metric="lift", min_threshold=1)  
  
# display information  
Print("Original Dataset:\n")  
Print(df.head())  
Print("\nFrequent  
Itemsets:\n")  
Print(frequent_itemsets)  
Print("\nAssociation  
Rules:\n") Print(rules)
```



Assignment-8)

Q. 1) Write a JavaScript to display message 'Exams are near, have you started preparing for?' (use alert

Box) and Accept any two numbers from user and display addition of two number .(Use Prompt and

Confirm box)

AAAns:

```
// Display message using alert box
```

```
Alert('Exams are near, have you started preparing for?');
```

```
// Accept two numbers from user using prompt and confirm
```

```
boxes Let num1 = prompt('Enter first number:');
```

```
Let num2 = prompt('Enter second number:');
```

```
Let confirmMsg = `Are you sure you want to add ${num1} and ${num2}?`;
```

```
// Show confirmation message to user using confirm
```

```
box Let confirmResult = confirm(confirmMsg);
```

```
// If user confirms, then perform addition and display the
```

```
result If (confirmResult) {
```

```
Num1 =
```

```
parseInt(num1); Num2
```

```
= parseInt(num2); Let
```

```
sum = num1 + num2;
```

```
Alert(`The sum of ${num1} and ${num2} is ${sum}.`);
```

```
}
```

Q. 2) Download the groceries dataset. Write a python program to read the dataset and display its



Information. Preprocess the data (drop null values etc.) Convert the categorical values into numeric

Format. Apply the apriori algorithm on the above dataset to generate the frequent itemsets and association

Rules

. Ans:

Import pandas as pd

From mlxtend.preprocessing import TransactionEncoder

From mlxtend.frequent_patterns import apriori, association_rules

Load the dataset

Df = pd.read_csv('market_basket.csv')

Drop any rows with null values

Df.dropna(inplace=True)

Convert categorical values to numeric

format Te = TransactionEncoder()

Te_ary = te.fit(df.values).transform(df.values)

Df = pd.DataFrame(te_ary, columns=te.columns_)

Generate frequent itemsets

Frequent_itemsets = apriori(df, min_support=0.01, use_colnames=True)

Generate association rules

Rules = association_rules(frequent_itemsets, metric="lift", min_threshold=1)

Display information about the dataset



```
Print("Dataset information:")
```

```
Print(df.info())
```

```
# Display the frequent itemsets
```

```
Print("\nFrequent itemsets:")
```

```
Print(frequent_itemsets)
```

```
# Display the association rules
```

```
Print("\nAssociation rules:")
```

```
Print(rules)
```

Assignment-9)

Q. 1) Write a JavaScript function to validate username and password for a membership form. Ans:

```
Function validateForm() {
```

```
// Get the username and password input values
```

```
Var username =
```

```
document.forms["membershipForm"]["username"].value; Var
```

```
password =
```

```
document.forms["membershipForm"]["password"].value;
```

```
// Validate username
```

```
If (username == "") {
```

```
Alert("Username must be filled  
out"); Return false;
```

```
}
```

```
// Validate password
```



```
If (password == "") {  
    Alert("Password must be filled  
    out"); Return false;  
}
```

```
// Return true if both username and password are  
valid Return true;  
}
```

Q. 2) Create your own transactions dataset and apply the above process on your dataset. Ans:

```
Items=['item1','item2','item3','item4']
```

```
Transactions = [ ['item1', 'item2', 'item3'],  
    ['item2', 'item3'],  
    ['item1', 'item2', 'item4'],  
    ['item1', 'item4'],  
    ['item2', 'item3', 'item4'],  
    ['item1', 'item3', 'item4'],  
    ['item1', 'item2'],  
    ['item1', 'item3'],  
    ['item3', 'item4'],  
    ['item2', 'item4']  
]
```

```
From mlxtend.preprocessing import TransactionEncoder
```

```
From mlxtend.frequent_patterns import apriori, association_rules
```



```
# Convert the transactions into a binary matrix  
Te = TransactionEncoder()  
Te_ary = te.fit_transform(transactions)  
  
# Convert the binary matrix into a pandas DataFrame  
Df = pd.DataFrame(te_ary, columns=te.columns_)  
  
# Generate frequent itemsets with a minimum support of 0.3  
Frequent_itemsets = apriori(df, min_support=0.3, use_colnames=True)  
  
# Generate association rules with a minimum confidence of 0.7  
Association_rules = association_rules(frequent_itemsets, metric="confidence", min_threshold=0.7)  
  
# Print the frequent itemsets and association rules  
Print(frequent_itemsets)  
Print(association_rules)
```

Assignment-10)

Q. 1) Create a HTML file to insert text before and after a Paragraph using jQuery. [Hint : Use before()

And after()].

Ans:

<!DOCTYPE html>



```
<html
>
<head
> <title>Insert text before and after paragraph using jQuery</title>
  <script src=https://code.jquery.com/jquery-3.6.0.min.js></script>
</head>
<body>
  <h1>Insert text before and after paragraph using jQuery</h1>

  <p>This is a paragraph.</p>

  <script>
    $(document).ready(function() {
      $("p").before("Text inserted before the paragraph. ");
      $("p").after(" Text inserted after the paragraph.");
    });
  </script>
</body>
</html>
```

Q2). Create the following dataset in python & Convert the categorical values into numeric format. Apply

The apriori algorithm on the above dataset to generate the frequent itemsets and association rules. Repeat

The process with different min_sup values.

```
TID={1:["eggs","milk","bread"],2=["eggs","apple"],3=["milk","bread"],4=["apple","milk"],5=["milk","apple","bread"]}
```

Ans:

```
Import pandas as pd
```

```
From mlxtend.preprocessing import TransactionEncoder
```

```
From mlxtend.frequent_patterns import apriori, association_rules
```

```
# Create the dataset
```

```
Dataset = {
```

```
    1: ["eggs","milk","bread"],
```

```
    2: ["eggs","apple"],
```

```
    3: ["milk","bread"],
```

```
    4: ["apple","milk"],
```

```
    5: ["milk","apple","bread"]
```

```
}
```

```
# Convert categorical values into numeric
```

```
format Te = TransactionEncoder()
```

```
Te_ary =
```

```
te.fit(dataset.values()).transform(dataset.values()) Df =
```

```
pd.DataFrame(te_ary, columns=te.columns_)
```

```
# Apply Apriori algorithm to generate frequent itemsets and association rules
```

```
Min_sup = 0.4
```

```
Frequent_itemsets = apriori(df, min_support=min_sup, use_colnames=True)
```

```
Association_rules = association_rules(frequent_itemsets, metric="confidence",  
min_threshold=0.6)
```

```
# Print the frequent itemsets and association rules
```



Print("Frequent Itemsets:\n", frequent_itemsets)

Print("\nAssociation Rules:\n", association_rules)

Assignment-11)

Q. 1) Write a Javascript program to accept name of student, change font color to red, font size to 18 if

Student name is present otherwise on clicking on empty text box display image which changes its size

(Use onblur, onload, onmouseover, onmouseleave,

onmouseup) Ans:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>JavaScript Example</title>
```

```
    <style>
```

```
        #name {
```

```
            Font-size:
```

```
            14px; Color:
```

```
            black;
```

```
        }
```

```
    </style>
```

```
</head>
```

```
<body>
```

```
    <input type="text" id="name" onblur="changeStyle()" onmouseover="changeSize()"  
onmouseout="resetSize()" onmousedown="changeColor()" onmouseup="resetColor()">
```

```
    <img id="img" src=https://via.placeholder.com/150 onload="changeImageSize()">
```

```
<script>
```

```
    Function changeStyle() {
```



```
Let name =  
document.getElementById("name").value; If  
(name) {  
    Document.getElementById("name").style.fontSize = "18px";  
    Document.getElementById("name").style.color = "red";  
} else  
{  
    Document.getElementById("img").style.display = "block";  
}  
}
```

```
Function changeSize() {  
    Document.getElementById("name").style.fontSize = "16px";  
}
```

```
Function resetSize() {  
    Document.getElementById("name").style.fontSize = "14px";  
}
```

```
Function changeColor() {  
    Document.getElementById("name").style.color = "blue";  
}
```

```
Function resetColor() {  
    Document.getElementById("name").style.color = "red";  
}
```

```
Function changeImageSize() {  
    Document.getElementById("img").style.width = "200px";  
    Document.getElementById("img").style.height = "200px";  
}
```



```
</script>
</body>
</html>
```

Q 2). Create the above dataset in python & Convert the categorical values into numeric format. Apply

The apriori algorithm on the above dataset to generate the frequent itemsets and association rules. Repeat

The process with different min_sup values.

TID={1:["butter", "bread", "milk"], 2=["butter", "flour", "milk", "suger"], 3=["butter", "eggs", "milk", "salt"], 4=["eggs"], 5=["butter", "flour", "milk", "salt"]}

Ans:

```
Import pandas as pd
```

```
From mlxtend.preprocessing import TransactionEncoder
```

```
From mlxtend.frequent_patterns import apriori, association_rules
```

```
# Creating the dataset
```

```
Dataset = [['butter', 'bread', 'milk'], ['butter', 'flour', 'milk', 'sugar'], ['butter', 'eggs', 'milk', 'salt'], ['eggs'], ['butter', 'flour', 'milk', 'salt']]
```

```
Df = pd.DataFrame(dataset)
```

```
# Converting the categorical values into numeric
```

```
format Te = TransactionEncoder()
```



```

Te_ary = te.fit(dataset).transform(dataset)
Df = pd.DataFrame(te_ary, columns=te.columns_)

# Generating frequent itemsets using Apriori algorithm with different min_sup values
Min_sup_values = [0.4, 0.3, 0.2]
For min_sup in min_sup_values:
    Frequent_itemsets = apriori(df, min_support=min_sup, use_colnames=True)
    Print("Frequent Itemsets with minimum support of", min_sup)
    Print(frequent_itemsets)

# Generating association rules
Rules = association_rules(frequent_itemsets, metric="confidence", min_threshold=0.7)
Print("Association Rules with minimum support of", min_sup)
Print(rules)

```

Assignment-12)

Q. 1) Write AJAX program to read contact.dat file and print the contents of the file in a tabular format

When the user clicks on print button. Contact.dat file should contain srno, name, residence number,

Mobile number, Address. [Enter at least 3 record in contact.dat file]

.

Ans:

Html file

```
<<!DOCTYPE html>
<html>
<head>
  <title>Contact List</title>
  <script src=https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js></script>
  <script src="script.js"></script>
</head>
<body>
  <button id="printBtn">Print Contacts</button>
  <br><br>
  <table id="contactTable">
    <thead>
      <tr>
        <th>Sr. No.</th>
        <th>Name</th>
        <th>Residence Number</th>
        <th>Mobile Number</th>
        <th>Address</th>
      </tr>
    </thead>
    <tbody>
      <!-- Contact list will be displayed here -->
    </tbody>
  </table>
</body>
</html>
```



Ajax file

```
$(document).ready(function() {  
    // Event listener for print button  
    $("#printBtn").click(function() {  
        // AJAX request to read contact.dat file  
        $.ajax({  
            url: "contact.dat",  
            dataType: "text",  
            success: function(data)  
            {  
                // Split the file contents into  
                lines Var lines =  
                data.split("\n");  
  
                // Iterate over each line and create a table  
                row Var tableRows = "";  
                For (var i = 0; i < lines.length; i++) {  
                    Var columns =  
                    lines[i].split(",");  
                    If (columns.length == 5) { // Only process valid rows  
                        tableRows += "<tr>";  
                        for (var j = 0; j < columns.length; j++) {  
                            tableRows += "<td>" + columns[j] + "</td>";  
                        }  
                        tableRows += "</tr>";  
                    }  
                }  
            }  
  
            // Add the table rows to the table body  
            $("#contactTable tbody").html(tableRows);  
        }  
    }
```



```

    },
    Error: function(jqXHR, textStatus, errorThrown) {
        Alert("Error: " + errorThrown);
    }
});
});
});

```

Q. 2) Create 'heights-and-weights' Data set . Build a linear regression model by identifying independent

And target variable. Split the variables into training and testing sets and print them. Build a simple linear

Regression model for predicting purchases.

Ans:

Import numpy as

np Import pandas

as pd

From sklearn.linear_model import LinearRegression

From sklearn.model_selection import train_test_split

Create a random dataset with 10 samples

Heights = np.random.normal(170, 10, 10)

Weights = np.random.normal(70, 5, 10)

Combine the two arrays into a single dataset

Dataset = pd.DataFrame({'Height': heights, 'Weight': weights})



```

# Split the dataset into training and testing sets

X_train, X_test, y_train, y_test = train_test_split(dataset['Height'], dataset['Weight'],
test_size=0.2, random_state=42)

# Create a Linear Regression model and fit it to the training
data Lr_model = LinearRegression()
Lr_model.fit(X_train.values.reshape(-1, 1), y_train)

# Print the model coefficients
Print('Model Coefficients:',
Lr_model.coef_)

# Predict the weights for the test data and print the
predictions Y_pred =
Lr_model.predict(X_test.values.reshape(-1, 1))
Print('Predictions:', y_pred)

```

Assignment-13)

Q. 1) Write AJAX program where the user is requested to write his or her name in a text box, and the

Server keeps sending back responses while the user is typing. If the user name is not entered then the

Message displayed will be, "Stranger, please tell me your name!". If the name is Rohit, Virat, Dhoni,

Ashwin or Harbhajan , the server responds with "Hello, master !". If the name is anything else, the

Message will be " , I don't know you!".

Ans:



Html file

```
<!DOCTYPE html>
<html>
<head>
  <title>AJAX Program</title>
  <script src=https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js></script>
</head>
<body>
  <label for="name">Enter your name:</label>
  <input type="text" id="name" name="name">
  <div id="response"></div>

  <script src="ajax.js"></script>
</body>
</html>
```

Ajax file

```
$(document).ready(function() {
  // Attach an event listener to the name input field
  $('#name').on('input', function() {
    // Get the name entered by the user
    Var name = $(this).val();

    // Send an AJAX request to the server
    $.ajax({
```



```

        url:
        'server.php',
        type: 'POST',
        data: { name: name },
        success:
        function(response) {
            // Update the response div with the server's response
            $('#response').html(response);
        }
    });
});
});

```

File name: Server.php

```
<?php
```

```
// Get the name entered by the user
```

```
$name = $_POST['name'];
```

```
// Check if the name is empty
```

```
If (empty($name)) {
```

```
    Echo 'Stranger, please tell me your name!';
```

```
}
```

```
// Check if the name is one of the master names
```

```
Else if ($name == 'Rohit' || $name == 'Virat' || $name == 'Dhoni' || $name == 'Ashwin' || $name == 'Harbhajan') {
```

```
    Echo 'Hello, master!';
```

```
}
```

```
// Otherwise, the server doesn't know the user
```



```
Else
{
    Echo $name . ' , I don\'t know you!';
}
}
```

Q. 2) Download nursery dataset from UCI. Build a linear regression model by identifying independent

And target variable. Split the variables into training and testing sets and print them. Build a simple linear

Regression model for predicting

purchases. Ans:

Import pandas as

pd Import numpy

as np

From sklearn.model_selection import train_test_split

From sklearn.linear_model import LinearRegression

Load the dataset

url = <https://archive.ics.uci.edu/ml/machine-learning-databases/nursery/nursery.data>

names = ['parents', 'has_nurs', 'form', 'children', 'housing', 'finance', 'social', 'health',

'class'] dataset = pd.read_csv(url, names=names)

Identify independent and target

variables X = dataset.drop('class',

axis=1)

Y = dataset['class']

Convert categorical variables into numerical variables using one-hot

encoding X = pd.get_dummies(X)

```

# Split into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)

# Build a linear regression model
Model = LinearRegression()
Model.fit(X_train, y_train)

# Print the coefficients of the
model    Print("Intercept:  ",
Model.intercept_)
Print("Coefficients:      ",
Model.coef_)

# Predict the target variable for the testing
set Y_pred = model.predict(X_test)

# Evaluate the model using Mean Squared Error
(MSE) Mse = np.mean((y_test - y_pred) ** 2)
Print("MSE: ", mse)

```

Assignment-14)

Q. 1) Create TEACHER table as follows TEACHER(tno, tname, qualification, salary). Write Ajax Program to select a teachers name and print the selected teachers details.

AAns:

Js file

<!DOCTYPE html>

<html>

```

<head>
    <title>Teacher Details</title>
    <script src=https://code.jquery.com/jquery-3.6.0.min.js></script>
</head>
<body>
    <select id="teacher-list">
        <option value="">--Select Teacher--</option>
        <option value="1">John Doe</option>
        <option value="2">Jane Smith</option>
        <option value="3">Bob Johnson</option>
    </select>
    <button id="submit-btn">Get Details</button>
    <div id="details"></div>

    <script>
        $(document).ready(function() {
            $('#submit-btn').click(function() {
                Var tno = $('#teacher-
                list').val(); If (tno == '') {
                    Alert('Please select a
                    teacher. '); Return;
                }
                $.ajax({
                    url: 'teacherdetails.php',
                    method: 'POST',
                    data: {tno: tno},
                    success: function(response) {
                        $('#details').html(response);
                    },
                },
            }
        )
    </script>

```



```

        Error: function(xhr, status, error) {
            Console.log(xhr.responseText);
        }
    });
});
});
</script>
</body>
</html>

```

Php file teacherdetails.php

```

<?php
// Connect to database
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "database_name";
$conn = mysqli_connect($servername, $username, $password, $dbname);

// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

// Retrieve selected teacher
details if (isset($_POST['tno'])) {
    $tno = $_POST['tno'];
    $sql = "SELECT * FROM TEACHER WHERE tno = '$tno'";
}

```



```

$result = mysqli_query($conn, $sql);

If (mysqli_num_rows($result) > 0) {
    $row = mysqli_fetch_assoc($result);
    Echo "Teacher Name: " . $row['tname'] .
    "<br>"; Echo "Qualification: " .
    $row['qualification'] . "<br>"; Echo "Salary: " .
    $row['salary'] . "<br>";
} else
{
    Echo "No data found.";
}
}

```

// Close database connection

Mysqli_close(\$conn);

?>

Q. 2) Create the following dataset in python & Convert the categorical values into numeric format. Apply

The apriori algorithm on the above dataset to generate the frequent itemsets and association rules. Repeat

The process with different min_sup_values.

TID={1:["apple", "mango", "banana"], 2=["mango", "banana", "cabbage", "carrots"], 3=["mango", "banana", "carrots"], 4=["mango", "carrots"]}AAAns:

From mlxtend.preprocessing import

TransactionEncoder From mlxtend.frequent_patterns

import apriori

Create the dataset

```
TID = {1:["apple", "mango", "banana"],  
      2:["mango", "banana", "cabbage", "carrots"],  
      3:["mango", "banana", "carrots"],  
      4:["mango", "carrots"]}
```

Convert the categorical values into numeric

```
format Te = TransactionEncoder()  
Te_ary = te.fit([TID[i] for i in TID]).transform([TID[i] for i in  
TID]) Df = pd.DataFrame(te_ary, columns=te.columns_)
```

Apply the apriori algorithm with different min_sup values

```
Min_sup_values = [0.25, 0.5, 0.75]  
For min_sup in min_sup_values:  
    Frequent_itemsets = apriori(df, min_support=min_sup,  
    use_colnames=True) Print("Frequent itemsets with min_sup =",  
    min_sup) Print(frequent_itemsets)  
    Print("\n")
```

Assignment-15)

Q. 1) Write Ajax program to fetch suggestions when is user is typing in a textbox. (eg like google Suggestions. Hint create array of suggestions and matching string will be displayed).

Ans:

```
<!DOCTYPE html>  
<html>  
<head>  
    <title>AJAX Auto Suggestions Example</title>
```



```

<script>
    Function fetchSuggestions(str)
        { If (str.length == 0) {
            Document.getElementById("suggestions").innerHTML = "";
            Return;
        }
        Var suggestions = ["apple", "banana", "cherry", "dates", "elderberry", "fig",
"grape", "honeydew", "kiwi", "lemon"];
        Var matches = [];
        For (var i = 0; i < suggestions.length; i++) {
            If (suggestions[i].toLowerCase().startsWith(str.toLowerCase())) {
                Matches.push(suggestions[i]);
            }
        }
        If (matches.length > 0) {
            Document.getElementById("suggestions").innerHTML =
matches.join("<br>");
        } else
        {
            Document.getElementById("suggestions").innerHTML = "No
suggestions
found";
        }
    }
</script>
</head>
<body>
    <input type="text" onkeyup="fetchSuggestions(this.value)">
    <div id="suggestions"></div>
</body>
</html>

```



Q. 2) Create the following dataset in python & Convert the categorical values into numeric format. Apply

The apriori algorithm on the above dataset to generate the frequent itemsets and association rules. Repeat

The process with different min_sup values.

No	Company	model	year
1.	Tata.	Nexon.	2017
2.	MG.	Astor.	2021
3.	Kia.	Seltos.	2019
4.	Hyundai.	Creta.	2015

Ans:

```
Import pandas as pd
```

```
# Create the dataset
```

```
Data = {'No': [1, 2, 3,  
4],  
        'Company': ['Tata', 'MG', 'Kia', 'Hyundai'],  
        'Model': ['Nexon', 'Astor', 'Seltos', 'Creta'],  
        'Year': [2017, 2021, 2019, 2015]}
```

```
Df = pd.DataFrame(data)
```

```
# Convert categorical values into numeric format
```

```
Df['Company'] = pd.Categorical(df['Company'])
```

```
Df['Model'] = pd.Categorical(df['Model'])
```

```
Df['Company'] = df['Company'].cat.codes
```

```
Df['Model'] = df['Model'].cat.codes
```

```
Print(df)
```

```
From mlxtend.frequent_patterns import apriori
```

```
From mlxtend.frequent_patterns import association_rules
```

```
# Generate frequent itemsets with min_sup = 0.5
```

```
Frequent_itemsets = apriori(df, min_support=0.5, use_colnames=True)
```

```
Print(frequent_itemsets)
```

```
# Generate association rules with min_threshold = 0.7
```

```
Association_rules = association_rules(frequent_itemsets, metric="confidence",  
min_threshold=0.7)
```

```
Print(association_rules)
```

Assignment-16)

Q. 1) Write Ajax program to get book details from XML file when user select a book name. Create XML

File for storing details of book(title, author, year, price).

Ans:

Xml file book_details.xml

```
<books>
```

```
  <book
```

```
  >
```

```
    <title>The Great Gatsby</title>
```

```
    <author>F. Scott Fitzgerald</author>
```



```
<year>1925</year>
<price>10.99</price>
</book>
<book>
  <title>To Kill a Mockingbird</title>
  <author>Harper Lee</author>
  <year>1960</year>
  <price>8.99</price>
</book>
<book>
  <title>1984</title>
  <author>George Orwell</author>
  <year>1949</year>
  <price>6.99</price>
</book>
<book>
  <title>Pride and Prejudice</title>
  <author>Jane Austen</author>
  <year>1813</year>
  <price>7.99</price>
</book>
</books>
```

Ajax file

```
<!DOCTYPE html>
<html>
<head>
```



```

<title>Book Details</title>
<script src=https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js></script>
<script>
    $(document).ready(function(){
        $("select").change(function()
            { Var book =
              $(this).val();
              $.ajax({
                  url:
                    "book_details.xml",
                  dataType: "xml",
                  success:
                    function(xml){
                        $(xml).find('book').each(function(){
                            Var title = $(this).find('title').text();
                            If (title == book) {
                                Var author =
                                  $(this).find('author').text();
                                Var year =
                                  $(this).find('year').text(); Var price
                                  = $(this).find('price').text();
                                $("#details").html("Author: " + author
                                  + "<br>Year: " + year + "<br>Price: " +
                                  price);
                            }
                        });
                    }
                });
            });
        });
    });
</script>
</head>
<body>

```



```
<select>
  <option>Select a book</option>
  <option>The Great Gatsby</option>
  <option>To Kill a Mockingbird</option>
  <option>1984</option>
  <option>Pride and Prejudice</option>
</select>
<div id="details"></div>
</body>
</html>
```

Q2). Consider any text paragraph. Preprocess the text to remove any special characters and digits.

Generate the summary using extractive summarization

pprocess. Ans:

Import re

Import

nlTK

From nltk.corpus import stopwords

From nltk.tokenize import sent_tokenize,

word_tokenize From heapq import nlargest

Sample text paragraph you can write any text

Text = "Natural language processing (NLP) is a subfield of linguistics, computer science, information engineering, and artificial intelligence concerned with the interactions between computers and human languages, in particular how to program computers to process and analyze large amounts of natural language data. Challenges in natural language processing frequently involve speech recognition, natural language understanding, and natural language generation. The history of natural language processing generally started in the 1950s, although work can be found from earlier periods."

```

# Remove special characters and
digits Text = re.sub('[^a-zA-Z]', ' ',
text)

# Tokenize the text into sentences
Sentences = sent_tokenize(text)

# Tokenize each sentence into words and remove stop
words Stop_words = set(stopwords.words('english'))
Words = []
For sentence in sentences:
    Words.extend(word_tokenize(sentence))
Words = [word.lower() for word in words if word.lower() not in stop_words]

# Calculate word frequency
Word_freq = nltk.FreqDist(words)

# Calculate sentence scores based on word
frequency Sentence_scores = {}
For sentence in sentences:
    For word in
        word_tokenize(sentence.lower()): If word
            in word_freq:
                If len(sentence.split(' ')) < 30:
                    If sentence not in sentence_scores:
                        Sentence_scores[sentence] =
                            word_freq[word]
                    Else:
                        Sentence_scores[sentence] += word_freq[word]

# Generate summary by selecting top 3 sentences with highest
scores

```



```
Summary_sentences = nlargest(3, sentence_scores, key=sentence_scores.get)
```

```
Summary = ' '.join(summary_sentences)
```

```
Print(summary)
```

Assignment-17)

Q. 1) Write a Java Script Program to show Hello Good Morning message onload event using alert box

And display the Student registration form.

Ans:

```
<!DOCTYPE html>
<html>
<head>
  <title>Student Registration Form</title>
  <script>
    Window.onload = function() {
      Alert("Hello Good Morning!");
    };
  </script>
</head>
<body>
  <h1>Student Registration Form</h1>
  <form>
    <label for="name">Name:</label>
    <input type="text" id="name" name="name" required><br><br>
    <label for="email">Email:</label>
```

```
<input type="email" id="email" name="email" required><br><br>
<label for="phone">Phone:</label>
<input type="tel" id="phone" name="phone" required><br><br>
<label for="address">Address:</label>
<textarea id="address" name="address" required></textarea><br><br>
<input type="submit" value="Submit">
</form>
</body>
</html>
```

Q. 2) Consider text paragraph. So, keep working. Keep striving. Never give up. Fall down seven times, get

Up eight. Ease is a greater threat to progress than hardship. Ease is a greater threat to progress than

Hardship. So, keep moving, keep growing, keep learning. See you at work. Preprocess the text to remove

Any special characters and digits. Generate the summary using extractive summarization process.

Ans:

Import re

From nltk.tokenize import sent_tokenize

Text paragraph

Text = "So, keep working. Keep striving. Never give up. Fall down seven times, get up eight. Ease is a greater threat to progress than hardship. Ease is a greater threat to progress than hardship. So, keep moving, keep growing, keep learning. See you at work."

Remove special characters and

**digits Text = re.sub('[^A-Za-z]+', '',
text)**

Tokenize the sentences

Sentences = sent_tokenize(text)

Calculate the score of each sentence based on the number of words # The sentences with more words will have a higher score

Scores = {}

For sentence in

sentences: Words =

sentence.split() Score

= len(words)

Scores[sentence] = score

Sort the sentences based on their scores

Sorted_sentences = sorted(scores.items(), key=lambda x: x[1], reverse=True)

Extract the top 2 sentences with the highest scores as the

summary Summary_sentences = [sentence[0] for sentence in

sorted_sentences[:2]] Summary = “.join(summary_sentences)

Print the

summary

Print(summary)

Assignment-18)

Q. 1) Write a Java Script Program to print Fibonacci numbers on onclick

event. Ans:

<!DOCTYPE html>



```

<html
>
<head
> <title>Fibonacci Numbers</title>
  <script>
    Function generateFibonacci() {
      // Get the input value from the user
      Var input =
document.getElementById("inputNumber").value; Var
output = document.getElementById("output");

      // Convert the input to a number
      Var n = parseInt(input);

      // Create an array to store the Fibonacci sequence
      Var fib = [];

      // Calculate the Fibonacci sequence up to n
      Fib[0] = 0;
      Fib[1] = 1;
      For (var i = 2; i <= n; i++) {
        Fib[i] = fib[i-1] + fib[i-
2];
      }

      // Display the Fibonacci sequence
      Output.innerHTML = "Fibonacci sequence up to " + n + ": " + fib.join(", ");
    }
  </script>
</head>
<body>
  <h1>Fibonacci Numbers</h1>

```



```
<p>Enter a number:</p>
<input type="text" id="inputNumber">
<button onclick="generateFibonacci()">Generate Fibonacci</button>
<p id="output"></p>
</body>
</html>
```

Q. 2) Consider any text paragraph. Remove the stopwords. Tokenize the paragraph to extract words and

Sentences. Calculate the word frequency distribution and plot the frequencies. Plot the wordcloud of the

Txt.

Ans:

Install the libraries

```
!pip install nltk matplotlib wordcloud
```

Import the necessary modules

```
Import nltk
```

```
From nltk.corpus import stopwords
```

```
From nltk.tokenize import word_tokenize,
```

```
sent_tokenize From nltk.probability import FreqDist
```

```
Import matplotlib.pyplot as plt
```

```
From wordcloud import
```

```
WordCloud
```

Download the stopwords corpus

```
Nltk.download('stopwords')
```

```
# Define the text paragraph
```

```
Text = "Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed tristique ante et velit vestibulum, vel pharetra orci iaculis. Nullam mattis risus quis augue tincidunt rhoncus. Morbi varius, arcu vitae scelerisque laoreet, magna est imperdiet quam, sit amet ultrices lectus justo id enim. Sed dictum suscipit commodo. Sed maximus consequat risus, nec pharetra nibh interdum quis. Etiam eget quam vel augue dictum dignissim sit amet nec elit. Nunc at sapien dolor. Nulla vitae iaculis lorem. Suspendisse potenti. Sed non ante turpis. Morbi consectetur, arcu a vestibulum suscipit, mauris eros convallis nibh, nec feugiat orci enim sit amet enim. Aliquam erat volutpat. Etiam vel nisi id neque viverra dapibus non non lectus."
```

```
# Tokenize the paragraph to extract words and sentences
```

```
Words = word_tokenize(text.lower())
```

```
Sentences = sent_tokenize(text)
```

```
# Remove the stopwords from the extracted words
```

```
Stop_words = set(stopwords.words('english'))
```

```
Filtered_words = [word for word in words if word.casefold() not in stop_words]
```

```
# Calculate the word frequency distribution and plot the frequencies using
```

```
matplotlib Fdist = FreqDist(filtered_words)
```

```
Fdist.plot(30, cumulative=False)
```

```
Plt.show()
```

```
# Plot the wordcloud of the text using wordcloud
```

```
Wordcloud = WordCloud(width = 800, height = 800,
```

```
Background_color = 'white',
```

```
Stopwords = stop_words,
```

```
Min_font_size = 10).generate(text)
```



```
# plot the WordCloud image
Plt.figure(figsize = (8, 8), facecolor = None)
Plt.imshow(wordcloud)
Plt.axis("off")
Plt.tight_layout(pad = 0)

Plt.show()
```

Assignment-19)

Q. 1) Write a Java Script Program to validate user name and password on onSubmit event. Ans:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Validate User Name and Password</title>
    <script>
      Function validateForm() {
        Var username =
          document.forms["myForm"]["username"].value; Var
          password = document.forms["myForm"]["password"].value;

        If (username == "") {
          Alert("Username must be filled out");
          Return false;
        }

        If (password == "") {
```



```
Alert("Password must be filled out");
Return false;
}
}
</script>
</head>
<body>
<h2>Validate User Name and Password</h2>
<form name="myForm" onsubmit="return validateForm()" method="post">
<label for="username">Username:</label>
<input type="text" id="username" name="username"><br><br>
<label for="password">Password:</label>
<input type="password" id="password" name="password"><br><br>
<input type="submit" value="Submit">
</form>
</body>
</html>
```

**Q. 2) Download the movie_review.csv dataset from Kaggle by using the following link
: https://www.kaggle.com/nltkdata/movie-review/version/3?select=movie_review.csv to perform**

Sentiment analysis on above dataset and create a wordcloud.

Ans:

Import pandas as pd

From textblob import TextBlob

From wordcloud import WordCloud,

STOPWORDS Import matplotlib.pyplot as plt



Load the dataset

```
Df = pd.read_csv('movie_review.csv')
```

Add a column for sentiment analysis using TextBlob

```
Df['Sentiment'] = df['Review'].apply(lambda x: TextBlob(x).sentiment.polarity)
```

Create a new dataframe for positive reviews only

```
Pos_df = df[df['Sentiment'] > 0.2]
```

Create a wordcloud for positive reviews

```
Wordcloud = WordCloud(width = 800, height =  
800,
```

```
Background_color
```

```
= 'white', Stopwords =
```

```
STOPWORDS,
```

```
Min_font_size = 10).generate(' '.join(pos_df['Review']))
```

Plot the wordcloud

```
Plt.figure(figsize = (8, 8), facecolor = None)
```

```
Plt.imshow(wordcloud)
```

```
Plt.axis("off")
```

```
Plt.tight_layout(pad = 0)
```

```
Plt.show()
```

Assignment-20)

Q. 1) create a student.xml file containing at least 5 student information. Ans:



```
<?xml version="1.0"?>
<students>
  <student>
    <name>John Doe</name>
    <age>21</age>
    <gender>Male</gender>
    <major>Computer Science</major>
    <gpa>3.8</gpa>
  </student>
  <student>
    <name>Jane Smith</name>
    <age>19</age>
    <gender>Female</gender>
    <major>Business</major>
    <gpa>3.5</gpa>
  </student>
  <student>
    <name>Tom Johnson</name>
    <age>20</age>
    <gender>Male</gender>
    <major>Engineering</major>
    <gpa>3.2</gpa>
  </student>
  <student>
    <name>Sara Lee</name>
    <age>22</age>
    <gender>Female</gender>
    <major>Psychology</major>
```



```
<gpa>3.6</gpa>
</student>
<student>
  <name>Mike Brown</name>
  <age>18</age>
  <gender>Male</gender>
  <major>Education</major>
  <gpa>3.4</gpa>
</student>
</students>
```

Q. 2) Consider text paragraph. """Hello all, Welcome to Python Programming Academy. Python Programming Academy is a nice platform to learn new programming skills. It is difficult to get enrolled

In this Academy. """ Remove the stopwords. Ans:

```
Import nltk
From nltk.corpus import stopwords
Nltk.download('stopwords')
```

Text paragraph

Text = "Hello all, Welcome to Python Programming Academy. Python Programming Academy is a nice platform to learn new programming skills. It is difficult to get enrolled in this Academy."

Tokenize the text

```
Tokens = nltk.word_tokenize(text)
```

Remove stopwords

Stop_words = set(stopwords.words('english'))

Filtered_tokens = [word for word in tokens if not word.lower() in stop_words]

Print the filtered tokens

Print(filtered_tokens)

Assignment-21)

Q. 1) Add a JavaScript File in Codeigniter. The Javascript code should check whether a number is

Positive or negative.

Ans:

Html file

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>Number Check</title>
```

```
<script src="<?php echo base_url('js/numberCheck.js'); ?>"></script>
```

```
</head>
```

```
<body>
```

```
<h1>Number Check</h1>
```

```
<p>Enter a number to check:</p>
```

```
<input type="number" id="num" />
```

```
<button onclick="checkNumber(document.getElementById('num').value)">Check</button>
```

```
</body>
```



</html>

Create is file check number.js

Function checkNumber(num)

```
{ If (num > 0) {  
    Alert("The number is positive.");  
} else if (num < 0) {  
    Alert("The number is negative.");  
} else {  
    Alert("The number is zero.");  
}  
}
```

Q. 2)Build a simple linear regression model for User

Data. Ans:

Import pandas as pd

From sklearn.model_selection import train_test_split

From sklearn.linear_model import LinearRegression

From sklearn.metrics import mean_squared_error, r2_score

Import matplotlib.pyplot as plt

1. Collect data

Data = pd.read_csv('user_data.csv')

2. Preprocess data

Data.dropna(inplace=True)

X = data['age'].values.reshape(-1, 1)



```
Y = data['income'].values.reshape(-1, 1)
```

3. Split data

```
X_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.2, random_state=0)
```

4. Train the model

```
Regressor = LinearRegression()
```

```
Regressor.fit(x_train, y_train)
```

5. Predict values

```
Y_pred = regressor.predict(x_test)
```

6. Evaluate model

```
Mse = mean_squared_error(y_test,  
y_pred) R2 = r2_score(y_test, y_pred)
```

```
Print("Mean squared error: ",  
mse) Print("R-squared: ", r2)
```

7. Visualize results

```
Plt.scatter(x_test, y_test,  
color='gray')  
Plt.plot(x_test, y_pred, color='red',  
linewidth=2) Plt.show()
```

Assignment-22)

Q. 1) Create a table student having attributes(rollno, name, class). Using codeigniter, connect to the

Database and insert 5 records in it.



Ans:

<?php

// Establish connection to PostgreSQL database

**\$conn = pg_connect("host=localhost dbname=your_database_name user=your_username
password=your_password");**

// Check if connection was

successful If (!\$conn) {

Echo "Connection failed.";

Exit;

}

// Create student table

\$query = "CREATE TABLE student (

Rollno INTEGER PRIMARY

KEY, Name VARCHAR(50)

NOT NULL, Class

VARCHAR(10) NOT NULL

);

\$result = pg_query(\$conn, \$query);

If (!\$result) {

Echo "Error creating table: " .

pg_last_error(\$conn); Exit;

} else {

**Echo "Table created successfully.
";**

}



```

// Insert 5 records into student table
$insert_query = "INSERT INTO student (rollno, name, class)
                VALUES (1, 'John Doe', '10A'),
                    (2, 'Jane Smith', '9B'),
                    (3, 'Bob Johnson', '11C'),
                    (4, 'Sarah Lee', '12D'),
                    (5, 'Tom Brown', '8E')";

$insert_result = pg_query($conn, $insert_query);

If (!$insert_result) {
    Echo "Error inserting records: " .
    pg_last_error($conn); Exit;
} else {
    Echo "Records inserted successfully.";
}

// Close database connection
Pg_close($conn);

?>

```

Q2). Consider any text paragraph. Remove the stopwords. Ans:

Import nltk

From nltk.corpus import stopwords



```
From nltk.tokenize import word_tokenize
```

```
# sample text paragraph
```

```
Text = "Hello all, Welcome to Python Programming Academy. Python Programming Academy is a nice platform to learn new programming skills. It is difficult to get enrolled in this Academy."
```

```
# tokenize the text
```

```
paragraph Words =  
word_tokenize(text)
```

```
# define stopwords
```

```
Stop_words = set(stopwords.words('english'))
```

```
# remove stopwords
```

```
Filtered_words = [word for word in words if word.casefold() not in stop_words]
```

```
# join filtered words to form a
```

```
sentence Filtered_sentence = '  
'join(filtered_words)
```

```
Print(filtered_sentence)
```

Assignment-23)

Q. 1) Create a table student having attributes(rollno, name, class) containing atleast 5 recodes . Using

Codeigniter, display all its records.

Ans:

```
<?php
```

```
// Establish connection to PostgreSQL database
```

```
$conn = pg_connect("host=localhost dbname=your_database_name user=your_username  
password=your_password");
```

```
// Check if connection was
```

```
successful If (!$conn) {
```

```
    Echo "Connection failed.";
```

```
    Exit;
```

```
}
```

```
// Create student table
```

```
$query = "CREATE TABLE student (
```

```
    Rollno INTEGER PRIMARY
```

```
    KEY, Name VARCHAR(50)
```

```
    NOT NULL, Class
```

```
    VARCHAR(10) NOT NULL
```

```
);
```

```
$result = pg_query($conn, $query);
```

```
If (!$result) {
```

```
    Echo "Error creating table: " .
```

```
    pg_last_error($conn); Exit;
```

```
} else {
```

```
    Echo "Table created successfully.<br>";
```

```
}
```

```
// Insert 5 records into student table
```

```
$insert_query = "INSERT INTO student (rollno, name, class)
```



```
VALUES (1, 'John Doe', '10A'),  
       (2, 'Jane Smith', '9B'),  
       (3, 'Bob Johnson', '11C'),  
       (4, 'Sarah Lee', '12D'),  
       (5, 'Tom Brown', '8E');
```

```
$insert_result = pg_query($conn, $insert_query);
```

```
If (!$insert_result) {
```

```
    Echo "Error inserting records: " .
```

```
    pg_last_error($conn); Exit;
```

```
} else {
```

```
    Echo "Records inserted successfully.";
```

```
}
```

```
// Close database connection
```

```
Pg_close($conn);
```

```
// function to display database records
```

```
Function display_records($table_name) {
```

```
    // establish connection to PostgreSQL database
```

```
    $conn = pg_connect("host=localhost dbname=your_database_name user=your_username  
password=your_password");
```

```
// check if connection was
```

```
successful If (!$conn) {
```

```
    Echo "Connection
```

```
failed."; Exit;
```



```

}

// retrieve records from specified table
$query = "SELECT * FROM " . $table_name;
$result = pg_query($conn, $query);

// check if query was
successful If (!$result) {
    Echo "Error retrieving records: " .
    pg_last_error($conn); Exit;
}

// display records in an HTML table
Echo "<table>";
Echo "<tr><th>Roll
No</th><th>Name</th><th>Class</th></tr>"; While ($row =
pg_fetch_assoc($result)) {
    Echo "<tr><td>" . $row['rollno'] . "</td><td>" . $row['name'] . "</td><td>" . $row['class'] .
"</td></tr>";
}
Echo "</table>";

// close database connection
Pg_close($conn);
}
?>

```

Q2). Consider any text paragraph. Preprocess the text to remove any special characters and Digits.

Ans:

Import re

Text = "Hello, #world123! This is a sample text paragraph. It contains special characters and 5 digits."

Remove special characters and digits

Processed_text = re.sub(r'^[a-zA-Zs]', "", text)

Print(processed_text)

Assignment-24)

Q. 1) Write a PHP script to create student.xml file which contains student roll no, name, address, college

And course. Print students detail of specific course in tabular format after accepting course as input.

Ans:

<?php

// Define student details

\$students = array(

Array("rollno" => 1, "name" => "John Doe", "address" => "123 Main St", "college" => "ABC College", "course" => "Computer Science"),

Array("rollno" => 2, "name" => "Jane Smith", "address" => "456 Main St", "college" => "DEF

```

College", "course" => "Information Technology"),
    Array("rollno" => 3, "name" => "Bob Johnson", "address" => "789 Main St", "college"
=> "GHI College", "course" => "Business Administration"),
    Array("rollno" => 4, "name" => "Sarah Lee", "address" => "101 Main St", "college" =>
"JKL College", "course" => "Marketing"),
    Array("rollno" => 5, "name" => "Tom Brown", "address" => "121 Main St", "college" =>
"MNO College", "course" => "Computer Science")
);

```

```

// Create a SimpleXMLElement object

```

```

$xml = new SimpleXMLElement('<students></students>');

```

```

// Add student elements to the XML object

```

```

Foreach ($students as $student) {
    $student_element = $xml->addChild('student');
    $student_element->addChild('rollno', $student['rollno']);
    $student_element->addChild('name', $student['name']);
    $student_element->addChild('address', $student['address']);
    $student_element->addChild('college', $student['college']);
    $student_element->addChild('course', $student['course']);
}

```

```

// Save the XML data to a file

```

```

$xml->asXML('student.xml');

```

```

// Get course input from user

```

```

$course = isset($_POST['course']) ? $_POST['course'] : "";

```

```

// Load the XML file

```

```

$xml = simplexml_load_file('student.xml');

```



```

// Find students with matching course
$filtered_students = $xml->xpath("//student[course='$course']");

// Print table of matching
students Echo "<table
border='1'>";

Echo "<tr><th>Roll
No</th><th>Name</th><th>Address</th><th>College</th><th>Course</th></tr>";

Foreach ($filtered_students as
    $student) { Echo "<tr>";
    Echo "<td>{$student-
>rollno}</td>"; Echo
    "<td>{$student->name}</td>";
    Echo "<td>{$student-
>address}</td>"; Echo
    "<td>{$student->college}</td>";
    Echo "<td>{$student-
>course}</td>"; Echo "</tr>";
}
Echo "</table>";
?>

```

Q. 2) Consider the following dataset :

<https://www.kaggle.com/datasnaek/youtubenew?select=INvideos.csv>

Write a Python script for the following :

i.

Read the dataset and perform data cleaning operations

on it. ii.

ii. Find the total views, total likes, total dislikes and comment count.



Ans:

Import pandas as pd

Read the dataset

Df = pd.read_csv('INvideos.csv')

Drop the columns that are not required

Df = df.drop(['video_id', 'trending_date', 'channel_title', 'category_id', 'publish_time', 'tags', 'thumbnail_link', 'comments_disabled', 'ratings_disabled', 'video_error_or_removed'], axis=1)

Convert the datatype of 'views', 'likes', 'dislikes', and 'comment_count' to integer

Df[['views', 'likes', 'dislikes', 'comment_count']] = df[['views', 'likes', 'dislikes', 'comment_count']].astype(int)

Find the total views, likes, dislikes, and comment count

Total_views = df['views'].sum()

Total_likes = df['likes'].sum()

Total_dislikes = df['dislikes'].sum()

Total_comments = df['comment_count'].sum()

Print('Total Views:', total_views)

Print('Total Likes:', total_likes)

Print('Total Dislikes:', total_dislikes)

Print('Total Comments:', total_comments)



Assignment-25)

Q. 1) Write a script to create "cricket.xml" file with multiple elements as shown below:

```
<CricketTeam>  
<Team country="Australia">  
<player>__</player>  
<runs>____</runs>  
<wicket>__</wicket>  
</Team>  
</CricketTeam>
```

Write a script to add multiple elements in "cricket.xml" file of category, country="India".

Ans:

```
<?php  
// Create a new DOM document  
$doc = new DOMDocument();  
  
// Create the root element  
$cricketTeam = $doc->createElement("CricketTeam");  
  
// Create the first team element for Australia  
$teamAustralia = $doc->createElement("Team");  
$teamAustralia->setAttribute("country", "Australia");  
  
// Create the player element and set its value  
$player1 = $doc->createElement("player", "Steve Smith");  
$teamAustralia->appendChild($player1);
```



```
// Create the runs element and set its value
$runs1 = $doc->createElement("runs", "7090");
$teamAustralia->appendChild($runs1);

// Create the wicket element and set its value
$wicket1 = $doc->createElement("wicket", "17");
$teamAustralia->appendChild($wicket1);

// Append the team element to the root element
$cricketTeam->appendChild($teamAustralia);

// Create the second team element for India
$teamIndia = $doc->createElement("Team");
$teamIndia->setAttribute("country", "India");

// Create the player element and set its value
$player2 = $doc->createElement("player", "Virat Kohli");
$teamIndia->appendChild($player2);

// Create the runs element and set its value
$runs2 = $doc->createElement("runs", "12169");
$teamIndia->appendChild($runs2);

// Create the wicket element and set its value
$wicket2 = $doc->createElement("wicket", "4");
$teamIndia->appendChild($wicket2);

// Create the category element and set its value
$category = $doc->createElement("category", "Captain");
```



```
$steamIndia->appendChild($category);  
  
// Append the team element to the root element  
$cricketTeam->appendChild($steamIndia);  
  
// Append the root element to the document  
$doc->appendChild($cricketTeam);  
  
// Save the XML file  
$doc->save("cricket.xml");  
  
Echo "Elements added successfully!";  
?>
```

Q. 2) Consider the following dataset :
https://www.kaggle.com/datasets/seungguini/youtube-commentsfor-covid19-relatedvideos?select=covid_2021_1.csv

Write a Python script for the following :

i.

Read the dataset and perform data cleaning operations

on it. ii.

ii. Tokenize the comments in words. iii. Perform sentiment analysis and find the percentage of positive, negative and neutral comments..

Ans:

Import pandas as pd

```

Import nltk
From nltk.sentiment.vader import SentimentIntensityAnalyzer

# read the dataset
Df = pd.read_csv('covid_2021_1.csv')

# remove null values and duplicates
Df.dropna(inplace=True)
Df.drop_duplicates(subset='Comment', inplace=True)

# tokenize comments in words
Nltk.download('punkt')
Df['tokens'] = df['Comment'].apply(nltk.word_tokenize)

# perform sentiment analysis
Nltk.download('vader_lexicon')
Sia = SentimentIntensityAnalyzer()
Df['sentiment'] = df['Comment'].apply(lambda x: sia.polarity_scores(x)['compound'])

# calculate percentage of positive, negative, and neutral
comments Total_comments = len(df)
Positive_comments = len(df[df['sentiment'] > 0])
Negative_comments = len(df[df['sentiment'] < 0])
Neutral_comments = len(df[df['sentiment'] == 0])
Positive_percentage = (positive_comments / total_comments) *
100
Negative_percentage = (negative_comments / total_comments) * 100
Neutral_percentage = (neutral_comments / total_comments) * 100

# print the results

```



Print('Total Comments:', total_comments)

Print('Positive Comments:', positive_comments, '(', positive_percentage, '%)')

Print('Negative Comments:', negative_comments, '(', negative_percentage, '%)')

Print('Neutral Comments:', neutral_comments, '(', neutral_percentage, '%)')

Assignment-26)

Q. 1) Create employee table as follows EMP (eno, ename, designation, salary). Write Ajax program to

Select the employees name and print the selected employee's details.

Ans:

Html file

```
<select id="employee-list">
```

```
  <option value="">Select an employee</option>
```

```
  <!--Populate this dropdown with employee names using PHP □
```

```
</select>
```

```
<div id="employee-details">
```

```
  <!--Employee details will be displayed here □
```

```
</div>
```

Ajax file

```
$(document).ready(function() {
```



```

// Add event listener to the select dropdown
$('#employee-list').change(function()
{ Var selectedEmployee =
$(this).val();
// Make an AJAX request to fetch employee details
$.ajax({
url:
'empdetails.php',
type: 'POST',
data: { employeeName: selectedEmployee },
dataType: 'json',
success: function(response) {
// Parse the JSON response and display employee details
Var detailsHtml = 'Employee Name: ' + response.ename +
'<br>' + 'Designation: ' + response.designation +
'<br>' + 'Salary: ' + response.salary;
$('#employee-details').html(detailsHtml);
},
Error: function(xhr, status, error) {
Console.log('Error:', error);
}
});
});
});

```

Php file as empdetails.php

```
<?php
```

```
// Establish database connection
```

```
$conn = pg_connect("host=localhost dbname=database_name user=username
password=password");
```



```

If (!$conn) {
    Die('Connection failed: ' . pg_last_error());
}

// Get the selected employee name from AJAX request
$employeeName = $_POST['employeeName'];

// Query the EMP table for the details of the selected employee
$sql = "SELECT * FROM EMP WHERE ename = '$employeeName'";
$result = pg_query($conn, $sql);

If (pg_num_rows($result) > 0) {
    // Build a JSON object with employee details
    $employee = pg_fetch_assoc($result);
    $response = array(
        'ename' => $employee['ename'],
        'designation' => $employee['designation'],
        'salary' => $employee['salary']
    );
    Echo json_encode($response);
} else {
    Echo "Employee not found";
}

// Close database connection
Pg_close($conn);
?>

```



Q. 2)Consider text paragraph. “””Hello all, Welcome to Python Programming Academy. Python Programming Academy is a nice platform to learn new programming skills. It is difficult to get enrolled

In this Academy.””” Preprocess the text to remove any special characters and digits. Generate the

Summary using extractive summarization process. Q.

Ans:

Import re

From nltk.tokenize import sent_tokenize

From sklearn.feature_extraction.text import TfidfVectorizer

From sklearn.metrics.pairwise import cosine_similarity

Text to summarize

Text = “Hello all, Welcome to Python Programming Academy. Python Programming Academy is a nice platform to learn new programming skills. It is difficult to get enrolled in this Academy.”

Preprocess the text to remove special characters and digits

Preprocessed_text = re.sub(r'[^\a-zA-Z\s]', '', text)

Tokenize the preprocessed text into sentences

Sentences = sent_tokenize(preprocessed_text)

Calculate the importance score of each sentence using TF-

IDF Vectorizer = TfidfVectorizer()

Tfidf_matrix = vectorizer.fit_transform(sentences)

Similarity_matrix = cosine_similarity(tfidf_matrix)

Select top N sentences based on their importance score

N = 2

Top_sentences = sorted(range(len(similarity_matrix[-1])), key=lambda i: similarity_matrix[-1][i])[- N:]

Concatenate the top sentences to form the

summary Summary = ''

For i in top_sentences:

Summary += sentences[i] + '

'

Print(summary)

Assignment-27)

Q. 1) Create web Application that contains Voters details and check proper validation for (name, Age, and nationality), as Name should be in upper case letters only, Age should not be less than 18 yrs and Nationality should be Indian.(use HTML-AJAX-PHP).

Ans :

Html file

<!DOCTYPE html>

<html>

<head>

<title>Voter Details</title>

<script src=<https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js>></script>

</head>

<body>

<h2>Voter Details</h2>



```

<form id="voterForm">
    <label for="name">Name:</label>
    <input type="text" id="name" name="name" required><br><br>
    <label for="age">Age:</label>
    <input type="number" id="age" name="age" required><br><br>
    <label for="nationality">Nationality:</label>
    <input type="text" id="nationality" name="nationality" required><br><br>
    <input type="submit" value="Submit">
</form>
<div id="response"></div>
<script>
    $(document).ready(function(){
        $('#voterForm').submit(function(event){
            Event.preventDefault();
            Var name =
            $('#name').val().toUpperCase(); Var age =
            $('#age').val();
            Var nationality = $('#nationality').val();
            $.ajax({
                url: 'voter.php',
                method: 'POST',
                data: {name: name, age: age, nationality: nationality},
                success: function(response){
                    $('#response').html(response);
                }
            });
        });
    });
</script>
</body>

```



</html>

Voter.php file

<?php

\$name = \$_POST['name'];

\$age = \$_POST['age'];

\$nationality = \$_POST['nationality'];

if(preg_match('/^[^A-Z]/', \$name)){

Echo 'Name should be in upper case letters only.';

} elseif(\$age < 18) {

Echo 'Age should not be less than 18 years.';

} elseif(strcasecmp(\$nationality, 'Indian') != 0) {

Echo 'Nationality should be Indian.';

} else {

**Echo 'Validation successful. Voter details:
Name: '.\$name.'
Age: '.\$age.'
Nationality: '.\$nationality;**

}

?>

Q. 2) Create your own transactions dataset and apply the above process on your dataset

Ans:

Import random

Import csv

Generate random transaction data



```

Transactions = []
For i in range(1,
    101):
    Transaction_id =
    i
    Transaction_date = f"2022-05-{random.randint(1, 31):02d}"
    Customer_id = random.randint(1, 10)
    Item_id = random.choice(["A", "B", "C"])
    Item_price = round(random.uniform(10.0, 100.0), 2)
    Quantity = random.randint(1, 10)
    Transactions.append([transaction_id, transaction_date, customer_id, item_id,
item_price, quantity])

# Save the data to a CSV file
With open("transactions.csv", 'w', newline=") as
    csvfile: Writer = csv.writer(csvfile)
    Writer.writerow(["Transaction ID", "Transaction Date", "Customer ID", "Item ID", "Item
Price", "Quantity"])
    For transaction in transactions:
        Writer.writerow(transaction)

Import pandas as pd

# Read the CSV file into a Pandas
DataFrame Df =
pd.read_csv("transactions.csv")

# Convert the "Item Price" column to numeric
type Df["Item Price"] = pd.to_numeric(df["Item
Price"])

```



Calculate the sales amount for each transaction

Df['Sales'] = df['Item Price'] * df['Quantity']

Group the transactions by customer ID and

calculate the total sales for each customer

Total_sales = df.groupby('Customer

ID')['Sales'].sum().reset_index()

Print the

results

Print(total_sales

)

Assignment-28)

Q. 1) Write a PHP script using AJAX concept, to check user name and password are valid or Invalid (use

Database to store user name and password).

Ans:

Html file

<!DOCTYPE html>

<html>

<head>

<title>Login</title>

<script src=<https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js>></script>

<script>

\$(document).ready(function(){



```
$("#login-  
form").submit(function(event){  
Event.preventDefault();  
Var username = $("#username").val();
```



```

        Var password = $("#password").val();
        $.ajax({
            url: 'check_login.php',
            type: 'post',
            data: {username: username, password:
                password}, success: function(response){
                    if(response == "valid"){
                        window.location.href = "dashboard.php";
                    }
                    Else
                    {
                        Alert("Invalid username or password");
                    }
                }
            });
        });
    });
</script>
</head>
<body>
    <h2>Login</h2>
    <form id="login-form" method="post">
        <label>Username:</label>
        <input type="text" name="username" id="username"><br><br>
        <label>Password:</label>
        <input type="password" name="password" id="password"><br><br>
        <input type="submit" value="Login">
    </form>
</body>

```



</html>

Php file as check_login.php

<?php

// Establish database connection

```
$conn = mysqli_connect('localhost', 'username', 'password',  
'database_name'); If (!$conn) {  
    Die('Connection failed: ' . mysqli_connect_error());  
}
```

// Get username and password from AJAX request

```
$username = $_POST['username'];  
$password = $_POST['password'];
```

// Query the users table for the entered username and password

```
$sql = "SELECT * FROM users WHERE username = '$username' AND password =  
'$password'";  
$result = mysqli_query($conn, $sql);
```

If (mysqli_num_rows(\$result) >

```
    0){ Echo "valid";  
} else {  
    Echo "invalid";  
}
```

// Close database connection

```
Mysqli_close($conn);  
?>
```



Q. 2) Build a simple linear regression model for Car Dataset.

Ans:

From sklearn.linear_model import LinearRegression

Mileage = [[10], [20], [30], [40], [50], [60], [70], [80]]

Price = [24, 19, 17, 13, 10, 7, 5, 2]

Reg = LinearRegression().fit(mileage, price)

Print('Intercept:', reg.intercept_)

Print('Coefficient:', reg.coef_[0])

New_mileage = [[25], [45], [65]]

Predicted_price =

reg.predict(new_mileage)

Print('Predicted prices:', predicted_price)

Assignment-29)

Q. 1) Write a PHP script for the following: Design a form to accept a number from the user. Perform the operations and show the results.

1) Fibonacci Series.

2) To find sum of the digits of that number. (Use the concept of self processing page.)

Ans:

```
<!DOCTYPE html>
<html>
<head>
    <title>Number Operations</title>
</head>
<body>
    <h1>Number Operations</h1>
    <?php
        // define variables and set to empty values
        $num = $op = "";

        If ($_SERVER["REQUEST_METHOD"] == "POST") {
            $num = test_input($_POST["num"]);
            $op = test_input($_POST["op"]);

            // perform operation based on user's choice
            Switch ($op) {
                Case "fib":
                    $result = fibonacci($num);
                    Echo "<p>The Fibonacci series of $num numbers is: $result</p>";
                    Break;
                Case "sum":
                    $result = sumOfDigits($num);
                    Echo "<p>The sum of digits in $num is: $result</p>";
                    Break;
                Default:
```



```
        Echo "<p>Invalid operation selected</p>";
    }
}
```

```
Function test_input($data) {
    $data = trim($data);
    $data = stripslashes($data);
    $data =
    htmlspecialchars($data); Return
    $data;
}
```

```
Function fibonacci($num) {
    $first = 0;
    $second = 1;
    $result = "";

    For ($i = 0; $i < $num; $i++) {
        $result .= $first . " ";
        $third = $first + $second;
        $first = $second;
        $second = $third;
    }

    Return $result;
}
```

```
Function sumOfDigits($num) {
    $sum = 0;
```



```

    While ($num > 0) {
        $digit = $num % 10;
        $sum += $digit;
        $num = (int)($num / 10);
    }

    Return $sum;
}
?>

```

```

<form method="post" action="<?php
echo
htmlspecialchars($_SERVER["PHP_SELF"]);?
">

    <label for="num">Enter a number:</label>
    <input type="number" name="num" id="num" required>
    <br><br>
    <label for="op">Select an operation:</label>
    <select name="op" id="op" required>
        <option value="">--Select--</option>
        <option value="fib">Fibonacci Series</option>
        <option value="sum">Sum of Digits</option>
    </select>
    <br><br>
    <input type="submit" value="Submit">
</form>

</body>
</html>

```

Q. 2) Build a logistic regression model for Student Score Dataset.



Ans:

Import necessary

libraries Import pandas

as pd

From sklearn.linear_model import

LogisticRegression From sklearn.model_selection

import train_test_split From sklearn.metrics import

accuracy_score

Load the dataset

Data = pd.read_csv('student_scores.csv')

Split the data into input and output

variables X = data.iloc[:, :-1].values

Y = data.iloc[:, -1].values

Split the data into training and testing sets

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=0)

Create the logistic regression model and fit it to the training data

Classifier = LogisticRegression()

Classifier.fit(X_train, y_train)

Make predictions on the testing set

Y_pred = classifier.predict(X_test)

Evaluate the model's accuracy

Accuracy = accuracy_score(y_test, y_pred)

Print("Accuracy:", accuracy)



Assignment-30)

Q. 1) Create a XML file which gives details of books available in “Bookstore” from following Categories.

1) Yoga

2) Story

3) Technical

And elements in each category are in the following format

<Book>

<Book_Title>

-----</Book_Title>

<Book_Author> -----</Book_Author>

<Book_Price>

-----</Book_Price>

</Book>

Save the file as “Bookcategory.xml”

.

Ans:

```
<?xml ve<?xml version="1.0" encoding="UTF-8"?>
```

```
<Bookstore>
```

```
<Yoga>
```

```
<Book>
```

```
<Book_Title>Light on Yoga</Book_Title>
```

```
<Book_Author>B.K.S. Iyengar</Book_Author>
```



<Book_Price>20.99</Book_Price>
</Book>
<Book>
<Book_Title>The Yoga Bible</Book_Title>
<Book_Author>Christina Brown</Book_Author>
<Book_Price>15.50</Book_Price>
</Book>
</Yoga>
<Story>
<Book>
<Book_Title>The Alchemist</Book_Title>
<Book_Author>Paulo Coelho</Book_Author>
<Book_Price>12.99</Book_Price>
</Book>
<Book>
<Book_Title>The Da Vinci Code</Book_Title>
<Book_Author>Dan Brown</Book_Author>
<Book_Price>14.75</Book_Price>
</Book>
</Story>
<Technical>
<Book>
<Book_Title>Python for Data Science Handbook</Book_Title>
<Book_Author>Jake VanderPlas</Book_Author>
<Book_Price>28.99</Book_Price>
</Book>
<Book>
<Book_Title>Cracking the Coding Interview</Book_Title>
<Book_Author>Gayle Laakmann McDowell</Book_Author>



```
<Book_Price>23.50</Book_Price>
</Book>
</Technical>
</Bookstore>
```

Q. 2) Create the dataset . transactions = [['eggs', 'milk', 'bread'], ['eggs', 'apple'], ['milk', 'bread'], ['apple',

'milk'], ['milk', 'apple', 'bread']] .

Convert the categorical values into numeric format. Apply the apriori algorithm on the above dataset to

Generate the frequent itemsets and association rules.

Ans:

```
Transactions = [['eggs', 'milk', 'bread'], ['eggs', 'apple'], ['milk', 'bread'], ['apple', 'milk'],
['milk', 'apple', 'bread']]
```

Create a dictionary to map items to unique numeric

```
values Item_to_num = {'eggs': 1, 'milk': 2, 'bread': 3, 'apple':
```

```
4}
```

Convert the categorical values in the dataset to numeric values

```
Numeric_transactions = []
```

For transaction in transactions:

```
    Numeric_transaction = [item_to_num[item] for item in transaction]
```

```
    Numeric_transactions.append(numeric_transaction)
```

```
Print(numeric_transactions)
```



From mlxtend.frequent_patterns import apriori, association_rules

Generate frequent itemsets with a minimum support of 0.4

Frequent_itemsets = apriori(numeric_transactions, min_support=0.4, use_colnames=True)

Generate association rules with a minimum confidence of 0.7

Rules = association_rules(frequent_itemsets, metric="confidence", min_threshold=0.7)

Print(frequent_itemset

s) Print(rules)

